

Persistent RAMDisk

Works on macOS Big Sur.

[Reference](#)

Persistence

There is a non-deprecated way to do it:

- Open the *Script Editor* app.
- Paste

```
do shell script "~/login"

on quit
  do shell script "~/logout"
  continue quit
end quit
```

- `File > Save`, Select `Application` and `Stay open after run handler` and `Save`
- `System Preferences > Users & Groups > Login Items tab > + button`
- Add the application and mark it as *Hidden*

To hide it from the Dock:

- Right-click the application and select *Show package contents*
- Open `Info.plist` and add

```
<key>NSUIElement</key>
<string>1</string>
```

Create RAMDisk scripts

```
$ touch ~/.login
$ touch ~/.logout
$ chmod +x ~/.login
$ chmod +x ~/.logout
```

Open `~/.login` and paste, this creates a 1GB RAMDisk

```
#!/usr/bin/env bash
diskutil erasevolume HFS+ "RAMDisk" `hdiutil attach -nomount ram://2097152` && rsync -rauL --
ignore-errors ~/.RAMDisk/ /Volumes/RAMDisk
```

Open `~/.logout` and paste

```
#!/usr/bin/env bash
rsync -rauL --delete --ignore-errors /Volumes/RAMDisk/ ~/.RAMDisk
```

- Mount the RAMDisk `$ ~/.login`
- The RAMDisk should appear in *Finder*.

Example use: PHPStorm caches on RAMDisk

1. Create a folder called *PHPStorm* on the RAMDisk.
2. Start `PHPStorm > Help > Edit custom properties...` and paste

```
idea.system.path=/Volumes/RAMDisk/PHPStorm
```

Created 2021-08-20 11:28:53 UTC by Sander

Updated 2021-08-20 12:41:22 UTC by Sander